



US006988394B2

(12) **United States Patent**
Shedd et al.

(10) **Patent No.:** **US 6,988,394 B2**
(45) **Date of Patent:** **Jan. 24, 2006**

(54) **APPARATUS AND METHOD OF PORTABLE
AUTOMATED BIOMONITORING OF WATER
QUALITY**

(75) Inventors: **Tommy R. Shedd**, Middletown, MD
(US); **Mark W. Widder**,
Chambersburg, PA (US); **Mark W.
Brown**, Myersville, MD (US); **Murray
S. Swanson**, Rockyridge, MD (US)

(73) Assignee: **The United States of America as
represented by the Secretary of the
Army**, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/774,639**

(22) Filed: **Feb. 3, 2004**

(65) **Prior Publication Data**

US 2004/0206162 A1 Oct. 21, 2004

Related U.S. Application Data

(60) Provisional application No. 60/444,202, filed on Feb.
3, 2003.

(51) **Int. Cl.**
G01N 33/18 (2006.01)
A01K 63/00 (2006.01)

(52) **U.S. Cl.** **73/61.41**; 73/864.91; 119/224;
119/226; 340/573.1; 340/573.6

(58) **Field of Classification Search** 73/61.41,
73/432.1, 864.91; 119/215, 224, 226; 340/573.1,
340/573.6
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,827,283 A * 8/1974 Lerner et al. 73/40

4,626,992 A	12/1986	Greaves et al.	
4,723,511 A	2/1988	Solman	
5,140,855 A	8/1992	Gruber	
5,307,052 A	4/1994	Harrison	
5,469,144 A	11/1995	Gradzki et al.	
5,804,705 A	9/1998	Florion et al.	73/61.41
6,058,763 A	5/2000	Shedd et al.	73/61.41
6,119,630 A	9/2000	Lobsiger et al.	
6,393,899 B1	5/2002	Shedd et al.	73/61.41

FOREIGN PATENT DOCUMENTS

GB	2195 543 A	4/1988
WO	WO 95/14925 A1	6/1995
WO	WO 98/41862	9/1998

OTHER PUBLICATIONS

ASTM Standard Guide for Ventilatory Behavioral Toxicology Testing of Freshwater Fish, E1768-95,9,ASTM, West Conshohocker, PA.

(Continued)

Primary Examiner—Daniel S. Larkin

(74) *Attorney, Agent, or Firm*—Elizabeth Arwine

(57) **ABSTRACT**

A portable automated biomonitoring system for monitoring water quality includes an exposure chamber for housing an aquatic organism and a water inlet for directing water to the exposure chamber. The aquatic organism has ventilatory behavior and body movement sensitive to water quality. Electrodes sense electrical signals produced by the organism during its ventilatory behavior and body movement, and a controller responsive to signals from the electrodes determines a plurality of ventilatory parameters based on the signals. The ventilatory parameters are compared with corresponding thresholds to determine when the water to which the organism is exposed has caused physiological stress to the organism. The water being evaluated may be recirculated through the system for further analysis.

19 Claims, 15 Drawing Sheets

